

CHEVRON PRODUCTS COMPANY GLOBAL LUBRICANTS -- CPS226502, DEXRON III SUPREME  
AUTOMATIC TRANSMISSION FLUID -- 9150-00-657-4959

===== Product Identification =====

Product ID:CPS226502, DEXRON III SUPREME AUTOMATIC TRANSMISSION FLUID  
MSDS Date:09/22/1999

FSC:9150

NIIN:00-657-4959

MSDS Number: CKVMC

=== Responsible Party ===

Company Name:CHEVRON PRODUCTS COMPANY GLOBAL LUBRICANTS

Address:555 MARKET ST. ROOM 803

City:SAN FRANCISCO

State:CA

ZIP:94105-2870

Country:US

Info Phone Num:800-414-6737/415-894-0434

Emergency Phone Num:800-231-0623

Resp. Party Other MSDS Num.:000021 REVISION #26

Chemtrec Ind/Phone:(800)424-9300

CAGE:2H740

=== Contractor Identification ===

Company Name:CASCADE DISTRIBUTING

Address:136 E. MAIN STREET SUITE 6

Box:City:KENT

State:OH

ZIP:44240

Country:US

Phone:330-677-1118/FAX 330-677-1014

Contract Num:SP0450-01-C-0605

CAGE:082N2

Company Name:CASCADE DISTRIBUTING

Address:136 E. MAIN STREET SUITE 6

Box:City:KENT

State:OH

ZIP:44240

Country:US

Phone:330-677-1118/FAX 330-677-1014

Contract Num:SP0450-01-C-0623

CAGE:082N2

Company Name:CHEVRON PRODUCTS CO GLOBAL LUBRICANTS

Address:555 MARKET STREET ROOM 803

Box:City:SAN FRANCISCO

State:CA

ZIP:94105-2870

Country:US

Phone:800-228-3500/415-894-0703

CAGE:2H740

===== Composition/Information on Ingredients =====

> Wt:80.

Ingred Name:DISTILLATES, HYDROTREATED HEAVY PARAFFINIC

CAS:64742-54-7

Code:F

RTECS #:PY8035500

OSHA PEL:5 MG/M3 (MIST)

ACGIH TLV:5 MG/M3 (MIST)

ACGIH STEL:10 MG/M3 (MIST)

Ingred Name:DISTILLATES (PETROLEUM), SOLVENT DEWAXED HEAVY PARAFFINIC

CAS:64742-65-0

Code:F

RTECS #:PY8038500  
 OSHA PEL:5 MG/M3 (MIST)  
 ACGIH TLV:5 MG/M3 (MIST)  
 ACGIH STEL:10 MG/M3 (MIST)

Ingred Name:DISTILLATES (PETROLEUM), SOLVENT-DEWAXED LIGHT PARAFFINIC  
 CAS:64742-56-9  
 RTECS #:PY8039500  
 OSHA PEL:5 MG/M3 (MIST)  
 ACGIH TLV:5 MG/M3 (MIST)

Ingred Name:DISTILLATES, SOLVENT-REFINED LIGHT NAPHTHENIC  
 CAS:64741-97-5  
 RTECS #:PY8041000  
 OSHA PEL:5 MG/M3 (MIST)  
 ACGIH TLV:5 MG/M3 (MIST)

===== Hazards Identification =====

LD50 LC50 Mixture:NOT DATA PROVIDED BY MANUFACTURER  
 Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
 Health Hazards Acute and Chronic:EYE: NOT EXPECTED TO CAUSE PROLONGED  
 OR SIGNIFICANT IRRITATION. SKIN: CONTACT WITH SKIN IS NOT EXPECTED  
 TO CAUSE PROLONGED OR SIGNIFICANT IRRITATION. NOR EXPECTED TO BE  
 HARMFUL TO INTERNAL ORGANS IF A BSORBED THROUGH THE SKIN.  
 ACCIDENTAL HIGH-VELOCITY INJECTION UNDER THE SKIN OF MATERIALS OF  
 THIS TYPE MAY RESULT IN SERIOUS INJURY. THE INITIAL WOUND AT THE  
 INJECTION SITE MAY NOT APPEAR TO BE SERIOUS AT FIRST, BUT, IF LEFT  
 UNATTENDED, COULD RESULT IN DISFIGUREMENT OR AMPUTATION OF THE  
 AFFECTED PART. INGESTION: NOT EXPECTED TO BE HARMFUL IF SWALLOWED.  
 INHALATION: MAY CAUSE RESPIRATORY IRRITATION O R OTHER PULMONARY  
 EFFECTS.  
 Explanation of Carcinogenicity:NONE OF THESE OILS REQUIRE A CANCER  
 WARNING UNDER OSHA 29 CFR 1910.1200. THESE OILS HAVE NOT BEEN  
 LISTED BY THE NTP OR IARC.  
 Effects of Overexposure:ACCIDENTAL HIGH-VELOCITY INJECTION UNDER THE  
 SKIN OF MATERIALS OF THIS TYPE MAY RESULT IN SERIOUS INJURY. THE  
 INITIAL WOUND AT THE INJECTION SITE MAY NOT APPEAR TO BE SERIOUS AT  
 FIRST, BUT, IF LEFT UN ATTENDED, COULD RESULT IN DISFIGUREMENT OR  
 AMPUTATION OF THE AFFECTED PART. INHALATION: MAY CAUSE RESPIRATORY  
 IRRITATION OR OTHER PULMONARY EFFECTS.  
 Medical Cond Aggravated by Exposure:NO DATA PROVIDED BY MANUFACTURER

===== First Aid Measures =====

First Aid:EYE: NO SPECIFIC FIRST AID MEASURES ARE REQUIRED. AS A  
 PRECAUTION REMOVE CONTACT LENSES, IF WORN, & FLUSH EYES WITH WATER.  
 SKIN: NO SPECIFIC FIRST AID MEASURES ARE REQUIRED BECAUSE THIS  
 MATERIAL IS NO T EXPECTED TO BE HARMFUL IF IT CONTACTS THE SKIN. AS  
 A PRECAUTION, REMOVE CLOTHING & SHOES IF CONTAMINATED. USE A  
 WATERLESS HAND CLEANER, MINERAL OIL, OR PETROLEUM JELLY TO REMOVE  
 THE MATERIAL, THEN W ASH WITH SOAP & WATER. WASH OR CLEAN  
 CONTAMINATED CLOTHING & SHOES BEFORE REUSE. INGESTION: NO SPECIFIC  
 FIRST AID MEASURES ARE REQUIRED.

===== Fire Fighting Measures =====

Flash Point Method:COC  
 Flash Point:=178.C, 352.4F  
 Autoignition Temp:Autoignition Temp Text:NDA  
 Lower Limits:NA  
 Upper Limits:NA  
 Extinguishing Media:CO2, DRY CHEMICAL, FOAM, WATER FOG.  
 Fire Fighting Procedures:THIS MATERIAL WILL BURN ALTHOUGH IT IS NOT  
 EASILY IGNITED.

Unusual Fire/Explosion Hazard:LEAK/RUPTURES IN HIGH PRESSURE SYSTEM  
 USING MATERIALS OF THIS TYPE CAN CREATE A FIRE HAZARD WHEN IN THE  
 VICINITY OF IGNITION SOURCES (EG OPEN FLAMES, PILOT LIGHTS, SPARKS,  
 OR ELECTRIC ARCS)..

===== Accidental Release Measures =====

Spill Release Procedures:STOP THE SOURCE OF LEAK OR RELEASE. CLEAN UP  
 RELEASES AS SOON AS POSSIBLE, OBSERVING PRECAUTIONS IN EXPOSURE  
 CONTROLS/PERSONAL PROTECTION. CONTAIN LIQUID TO PREVENT FURTHER  
 CONTAMINATION OF SOIL, SURFACE WATER OR GROUNDWATER. CLEAN UP  
 SMALL SPILLS USING APPROPRIATE TECHNIQUES SUCH AS SORBENT MATERIALS  
 OR PUMPING. WHERE FEASIBLE & APPROPRIATE, REMOVE CONTAMINATED SOIL.  
 FOLLOW PRESCRIBED PROCEDURES.

Neutralizing Agent:NO DATA PROVIDED BY MANUFACTURER

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT USE IN HIGH PRESSURE SYSTEMS IN  
 THE VICINITY OF FLAMES, SPARKS & HOT SURFACES. USE ONLY IN WELL  
 VENTILATED AREAS. KEEP CONTAINER CLOSED. CONTAINER IS NOT DESIGNED  
 TO CONTAIN PRESSURE. DO NOT USE PRESSURE TO EMPTY CONTAINER OR IT  
 MAY RUPTURE WITH EXPLOSIVE FORCE.

Other Precautions:EMPTY CONTAINERS RETAIN PRODUCT RESIDUE & CAN BE  
 DANGEROUS. DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL,  
 GRIND OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC  
 ELECTRICITY OR OTHER SOURCE OF IGNITION. THEY MAY EXPLODE & CAUSE  
 INJURY OR DEATH.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NO RESPIRATORY PROTECTION IS NORMALLY REQUIRED.  
 IF USER OPERATIONS GENERATE AN OIL MIST, DETERMINE IF AIRBORNE  
 CONCENTRATIONS ARE BELOW THE RECOMMENDED MINERAL OIL EXPOSURE  
 LIMITS. IF NOT WEAR A NIOSH APPROVED RESPIRATOR THAT PROVIDES  
 ADEQUATE PROTECTION FROM MEASURED CONCENTRATIONS OF THIS  
 MATERIAL. USE THE FOLLOWING ELEMENTS FOR ALL AIR-PURIFYING  
 RESPIRATOR

Ventilation:USE IN A WELL VENTILATED AREA. IF USER GENERATES AN OIL  
 MIST, USE PROCESS ENCLOSURES, LOCAL EXHAUST VENTILATION, OR OTHER  
 ENGINEERING CONTROLS TO CONTROL

Protective Gloves:, , <4H>

Eye Protection:WHERE SPLASHING IS POSSIBLE, WEAR SAFETY GLASSES WITH  
 SIDE SHIELDS

Other Protective Equipment:WHERE SPLASHING IS POSSIBLE, SELECT  
 PROTECTIVE CLOTHING DEPENDING ON OPERATIONS CONDUCTED, PHYSICAL  
 REQUIREMENTS AND OTHER SUBSTANCES.

Work Hygienic Practices:NO DATA PROVIDED BY MANUFACTURER

Supplemental Safety and Health

RESPIRATORY: PARTICULATE. VENTILATION: AIRBORNE LEVELS BELOW THE  
 RECOMMENDED MINERAL OIL MIST EXPOSURE LIMITS.

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:NDA

Melt/Freeze Pt:M.P/F.P Text:NDA

Decomp Temp:Decomp Text:NP

Spec Gravity:0.69

pH:NDA

Solubility in Water:INSOLUBLE

Appearance and Odor:RED LIQUID

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES  
 MAY REACT WITH STRONG OXIDIZING AGENTS, SUCH AS CHLORATES, NITRATES,  
 PEROXIDES, ETC.  
 Stability Condition to Avoid: NO DATA AVAILABLE.  
 Hazardous Decomposition Products: NO DATA AVAILABLE.

===== Toxicological Information =====

Toxicological Information: ACUTE SKIN/EYES/INHALATION/ORAL EFFECTS:  
 HAZARDS BASED ON DATA FOR SIMILAR MATERIAL. ADDITIONAL TOXICOLOGY  
 INFORMATION: THIS PRODUCT CONTAINS PETROLEUM BASE OILS WHICH MAY BE  
 REFINED BY VARIOUS PROCESSES INCLUDING SEVERE SOLVENT EXTRACTION,  
 SEVERE HYDROCRACKING, OR SEVERE HYDROTREATING. NONE OF THESE OILS  
 REQUIRE A CANCER WARNING UNDER OSHA 29 CFR 1910.1200. THESE OILS  
 HAVE NOT BEEN LISTED BY THE NTP OR IARC AS: CARCINOGENIC TO HUMANS  
 (GROUP 1); PROBABLY CARCINOGENIC TO HUMANS (GROUP 2A); OR POSSIBLY  
 CARCINOGENIC TO HUMANS (GROUP 2B)

===== Ecological Information =====

Ecological: ECOTOXICITY: NO DATA AVAILABLE. ENVIRONMENTAL FATE: THIS  
 MATERIAL IS NOT EXPECTED TO BE READILY BIODEGRADABLE.

===== Disposal Considerations =====

Waste Disposal Methods: OIL COLLECTION SERVICES ARE AVAILABLE FOR USED  
 OIL RECYCLING OR DISPOSAL. PLACE CONTAMINATED MATERIALS IN  
 CONTAINERS AND DISPOSE OF IN A MANNER CONSISTENT WITH APPLICABLE  
 REGULATIONS. CONTACT YOUR SALES REPRESENTATIVE OR LOCAL  
 ENVIRONMENTAL OR HEALTH AUTHORITIES FOR APPROVED DISPOSAL OF  
 RECYCLING METHODS.

===== MSDS Transport Information =====

Transport Information: DOT SHIPPING NAME: NONE. DOT HAZARD CLASS: NONE.  
 DOT IDENTIFICATION: NONE. DOT PACKING GROUP: N/A. ADDITIONAL INFO:  
 PETROLEUM LUBRICATING OIL - NOT HAZARDOUS BY US DOT. ADR/RID HAZARD  
 CLASS: NOT APPLICABLE

===== Regulatory Information =====

SARA Title III Information: SARA 311 CATEGORIES: IMMEDIATE (ACUTE)  
 HEALTH EFFECTS: NO; DELAYED (CHRONIC) HEALTH EFFECTS; FIRE HAZARD:  
 NO; SUDDEN RELEASE OF PRESSURE HAZARD: NO; REACTIVITY: NO.  
 Federal Regulatory Information: NO DATA PROVIDED BY MANUFACTURER  
 State Regulatory Information: THE FOLLOWING COMPONENTS OF THIS MATERIAL  
 ARE FOUND ON THE REGULATORY LISTS INDICATED: DISTILLATES,  
 SOLVENT-REFINED LIGHT NAPHTHENIC-MASS RTK; DISTILLATES (PETROLEUM),  
 HYDROTREATED LIGHT PARAFFINIC-MASS RTK; DISTILLATES (PETROLEUM),  
 SOLVENT DEWAXED LIGHT PARAFFINIC-MASS RTK. NEW JERSEY RIGHT-TO-KNOW  
 ACT L, 1983 CHAPTER 313 NJSA 34:5A-1, ET SEQ; THE PRODUCT IS TO BE  
 IDENTIFIED AS FOLLOWS: PETROLEUM OIL.

===== Other Information =====

Disclaimer (provided with this information by the compiling agencies):  
 This information is formulated for use by elements of the Department  
 of Defense. The United States of America in no manner whatsoever,  
 expressly or implied, warrants this information to be accurate and  
 disclaims all liability for its use. Any person utilizing this  
 document should seek competent professional advice to verify and  
 assume responsibility for the suitability of this information to their  
 particular situation.